



PRODUCT DESCRIPTION

Face Plates - 1, 2, 3, 4, or 6 port configurations that can accept Category 6 or Category 5e Keystone Jacks or Couplers.

Mounting Box - Single Gang, that accept the above face plates.

FEATURES	
Certifications & Compliance	RoHS Reach ISO 9001 ISO 14001 UL – Safety
Packaging	Poly Bag
Options	
Faceplates	White Ivory
Mounting Box	White

DESCRIPTION	PRODUCT ID
Faceplate, Plastic, 1 Port, White	FPKYSJWH01P0
Faceplate, Plastic, 2 Port, White	FPKYSJWH02P0
Faceplate, Plastic, 3 Port, White	FPKYSJWH03P0
Faceplate, Plastic, 4 Port, White	FPKYSJWH04P0
Faceplate, Plastic, 6 Port, White	FPKYSJWH06P0
Faceplate, Plastic, 1 Port, Ivory	FPKYSJIV01P0
Faceplate, Plastic, 2 Port, Ivory	FPKYSJIV02P0
Faceplate, Plastic, 3 Port, Ivory	FPKYSJIV03P0
Faceplate, Plastic, 4 Port, Ivory	FPKYSJIV04P0
Faceplate, Plastic, 6 Port, Ivory	FPKYSJIV06P0
Mounting Box, Single Gang, White	MBGANGWH0010

Product Images Shown Are For Illustration Purposes Only

FACE PLATE SPECIFICATIONS

Material	ABS, UL94V-0	
Dimensions	Height	4.49 in (114 mm)
	Width	2.76 in (70 mm)
	Depth	0.38 in (9.70 mm)
Operating Temperature Range	+14 °F to +140 °F (-10 °C to +60 °C)	
Storage Temperature Range	-40 °F to +154 °F (-40 °C to +68 °C)	
Humidity	10 % to 90 % RH	
Colors	White Ivory	
Package Contents	Face Plate Two 6-32 X 25 mm Screws (slotted, countersunk)	

SINGLE GANG MOUNTING BOX SPECIFICATIONS

Material	ABS, UL94V-0	
Dimensions	Height	4.54 in (115.20 mm)
	Width	2.83 in (72 mm)
	Depth	1.50 in (38 mm)
Operating Temperature Range	+14 °F to +140 °F (-10 °C to +60 °C)	
Storage Temperature Range	-40 °F to +154 °F (-40 °C to +68 °C)	
Humidity	10 % to 90 % RH	
Colors	White	
Package Contents	Single Gang Box Two Nylon Cable Ties Two 6-32 X 20 mm Screws Two 6-32 X 25 mm Screws (slotted, countersunk)	