




MATERIAL

PANEL : SPCC.
PLASTIC FRAME : ABS,UL94V-0.
CONTACT HOLDER : ABS,UL94V-0.
JACK CONTACTS : PHOSPHOR BRONZE,50U" GOLD PLATING.
IDC PLASTIC : PC,UL94V-0.
IDC CONTACT : PHOSPHOR BRONZE,TIN OVER NICKEL UNDERCOAT.
WIRE MANAGEMENT HOLDER : SPCC.
WIRE MANAGEMENT HANGER : SPCC.

PHYSICAL CHARACTERISTICS

SUITABLE IMPACT TOOL : 110/KRONE STYLE PUNCH DOWN TOOL.
INSERTION LIFE : 750 MATING CYCLES WITH FCC COMPLIANT 8P PLUG.
CONTACT FORCE : 100 GRAMS WITH FCC COMPLIANT 8P PLUG.
PLUG RETENTION FORCE : 11 LBF MIN.
DURABILITY : 200 TERMINATION CYCLES.
CONTACT COMPATIBILITY : ACCOMMODATES 22 TO 24 AWG SOLID.
OPERATING TEMPERATURE RANGE : -10°C TO 60°C.
STORAGE TEMPERATURE RANGE : -40°C TO 68°C.
HUMIDITY : 10%-90%RH.

ELECTRICAL

INSULATION RESISTANCE : 500 MΩ.
DIELECTRIC WITHSTANDING VOLTAGE : 1000 V AC.
DC CURRENT RATING : 1.5 Amps.
DC RESISTANCE : 0.1Ω.
CONTACT RESISTANCE : 20mΩ.

NOTE

• ONLY ACCEPTS RJ-45 8P8C PLUG.




ACCORDING TO : ANSI/TIA-568-C.2
ISO/IEC 11801 2nd Edition
IEC 60603-7


ENCLOSURE

Nylon Cable Tie X 8 PCS
Cable Tie Bar X 1 PC
Instructions X 1 PC

Cat 5e

56Y4
E491065



Scale	2:3			
3rd Angle Projection				
Unit	mm			
Date	2017/3/17			
Tolerance				
~20	~50	~150	150~	ANGLE
±0.2	±0.4	±0.5	±1.5	±2°

All Copy Rights Reserved	
nFlexon LLC	
Title	24 Port Category 5e Patch Panel
PP5ESTBK24P0	