



PRODUCT DESCRIPTION

Surface Mount Boxes can be used in lieu of wall mounted Jacks in locations where office cubicles are installed or where frequent office layout changes occur. The SMBs are blank, and can be outfitted with either Category 6 or Category 5e Keystone Jacks.


FEATURES	
Certifications & Compliance	RoHS Reach ISO 9001 ISO 14001
Packaging	Poly Bag
Options	White

DESCRIPTION	PRODUCT ID		
Surface Mount Box, 1 Port, White	SMKYSJWH01P0		
Surface Mount Box, 2 Port, White	SMKYSJWH02P0		
Surface Mount Box, 4 Port, White	SMKYSJWH04P0		
Surface Mount Box, 6 Port, White	SMKYSJWH06P0		

Note: These SMBs are blank. Keystone Jacks need to be ordered separately.

Product Images Shown Are For Illustration Purposes Only

PRODUCT SPECIFICATIONS





SURFACE MOUNT BOXES S	PECIFICATIONS							
Material	Housing							
	Shutter-Upper	ABS, UL94V-0						
	Shutter-Lower							
	Spring	Stainless						
	Screw	Slotted Philips Cross Recessed Binding Head (3.50 X 20 mm) Self Taping Nickel Plated						
Operating Temperature Range	+14 °F to +140 °F (+14 °F to +140 °F (-10 °C to +60 °C)						
Storage Temperature Range	-40 °F to +154 °F (-	-40 °F to +154 °F (-40 °C to +68 °C)						
Humidity	10 % to 90 % RH	10 % to 90 % RH						
Color	White	White						
Dimensions		1 Port	2 Port	4 Port	6 Port			
	Height	2.57 in (65.2 mm)	2.56 in (65 mm)	2.58 in (65.5 mm)	2.58 in (65.5 mm)			
	Width	1.89 in (48 mm)	3.00 in (76 mm)	5.20 in (132 mm)	7.38 in (187.5 mm)			
	Depth	1.03 in (26.20 mm)	1.04 in (26.40 mm)	1.18 in (30 mm)	1.18 in (30 mm)			
Package Contents	Surface Mount Box	1	1	1	1			
	Cable Tie(s)	1	2	4	6			
	ID ICON PC	1	2	4	6			
	ID ICON Tel	1	2	4	6			
	ID Paper	1	1	1	1			
	Screws	2	2	2	2			
	Transparent ID Cover	1	1	1	1			
	Twin Adhesive	1	1	1	1			